

GLOSS FINISHING WAX



Product Description

Our best selling Gloss Finishing Wax is a carefully designed combination of carnauba and microcrystalline waxes suspended in a low odour solvent to enable you to build up a super-tough glossy finish to turned work that is also fingerprint resistant Food & Toy Safe when cured.

It has a stiff texture and at times (particularly in cold weather) may appear 'crumbly' in the tin. This is perfectly normal and is due to the very high wax to solvent ratio. When used correctly, you need less of the product than you may think to achieve a fantastic quality finish.

We believe our Gloss Finishing Wax is the toughest and most long lasting finish available and is a popular go-to finish for many turners. Supplied in a 130g (4.4oz) lacquered lever lid tin.

Click for Information and Videos at www.hampshiresheen.com

Basic Application

- 1: Sand piece immaculately down to at least 400 grit;
- 2: For best results, apply sanding sealer and burnish when dry;
- 3: Evenly apply a light coat of the wax with a soft paper towel;
- 4: Allow to dry a little and then buff. (Drying times vary, depending on ambient temperature and humidity;
- 5: Apply additional coats for a deeper shine.

Follow Us

For advice, videos, downloads, live demos and to contact us for tech support, search 'Hampshire Sheen' on Facebook, Instagram and YouTube. You can also tag us using # or @ hampshiresheen to share your work with us.

Always read the product labels.

This guide has been produced for Hampshire Sheen Ltd by Martin Saban-Smith RPT. Copyright © 2021. Registered in England no. 09817729. Garthowen Garden Centre, Alton Lane, Four Marks, Hampshire. GU34 5AJ. United Kingdom. V1.0/0321

PRO FINISHING TIPS

- Always use a sanding sealer for decorative items.
 - Apply with paper towel.
 - Use less than you think you need.
 - Best applied with the lathe stationary.
 - Build the product up in *light* layers.
- Buff to a shine with the lathe spinning at an appropriate speed for the size and shape of the piece.
 - Can be mechanically buffed with a dry buffing wheel.
- Take your time! It's the quality of the finish that will be seen for the length of the piece's life.
- Getting lines when applying? Too much heat! Sand back, reapply and use less pressure. Or use a heat gun (with caution!).
- White flecks in open grain wood? Use a heat gun to melt them, then buff again. Use less next time.
 - Can be used to overcoat Embellishing Waxes and is compatible with other finishing products.
 - Firmly replace the lid after use.
- Store in a cool dry place out of direct light, away from heat sources and protect from freezing.
 - Do not attempt to soften it the process is dangerous.
- Once opened and stored correctly, the product will be good for use for 18 months +.
 - All wax products will tarnish if left in contact with water or acids such as fruit or alcohol.

SAFETY FIRST! Always take appropriate steps to ensure the safety of your workshop environment.