

CLEAR & BLACK GLOSS LACQUERS

Product Description

Our gloss acrylic Spray Lacquers have been formulated to be strong and flexible. They can be used for both internal and external projects, and look sublime when burnished to a flawless shine.

Touch dry in 10 to 20 minutes, these lacquers can be overcoated after that time, and lightly burnished within a few of hours under normal conditions. Leave to fully cure over night before using a buffing system.

Use over the top of our Intrinsic Colour Collection and sanding sealer for vibrant, attractive and well protected pieces.

These lacquers have been chosen for superb qualities to bring you a first class finishing product: Fast drying and high gloss; Can be used on wood, metal and other media; Weather resistant, light proof and UV resistant; Scratch and impact resistant; Excellent surface hardness and good elasticity. Perfect for wood projects; Can be mechanically buffed. Coverage: 1.56 - 2.19m² per 500ml

Our lacquers are 100% free from heavy metals. The caps and packaging are made of recyclable materials. Supplied in a 500ml (17.6oz) aerosol cans with 2 diffusing nozzles.



Click for Information and Videos at www.hampshiresheen.com

Basic Application

- 1: Sand your work down smooth and ensure the surface is free from dust, grease and moisture;
- 2: Prepare the surface well with a suitable sealer and ensure it has fully dried;
- 3: Shake can for at least two minutes before use;
- 4: Take care to avoid breathing spray and use in a well ventilated area;
- 5: Apply light coats 250mm from the piece, giving time for the lacquer to dry between coats;
- 6: If desired, lightly cut back the lacquer between dry coats for an even finish;
- 7: When dry and under normal conditions, Hampshire Sheen lacquers can be burnished with abrasive pastes and mechanically buffed after approximately 24 hours.
- 8: Apply an additional overcoat of our Microcrystalline Wax for a silky smooth feel.

Follow Us

For advice, videos, downloads, live demos and to contact us for tech support, search 'Hampshire Sheen' on Facebook, Instagram and YouTube. You can also tag us using # or @ hampshiresheen to share your work with us.

Always read the product labels.

This guide has been produced for Hampshire Sheen Ltd by Martin Saban-Smith RPT. Copyright © 2021. Registered in England no. 09817729. Garthowen Garden Centre, Alton Lane, Four Marks, Hampshire. GU34 5AJ. United Kingdom. V1.0/0321

PRO FINISHING TIPS

- For a glass-like lacquer finish, do not expect a quick process. It takes time and patience!
- A poorly sealed surface will require more lacquer to cover it. Ensure you seal your piece properly!
- When applying the first few coats, it is normal for lacquers to look a bit like orange peel. This will even out during further application.
- For best results, cut the surface back after every 2 or 3 coats to even out the orange peel look. Use 400 grit paper or a soft abrasive pad.
- Each coat should lightly cover the entire surface. Too much, and the product will not lay evenly.
- If you get a run through applying too much, allow it to dry completely, then sand that area back or cut it all off and start again before reapplying.
- When cured, and for a glass-like finish, use abrasive pastes like Yorkshire Grit and finish off with an automotive paint restoring cream.
 - Be careful when using abrasives and pastes on lacquers - too much heat can cause them to melt and slide. Take your time.
 - Clear the nozzle by spraying the product upside down, then replacing the lid after use.
- Store in a cool dry place out of direct light, away from heat sources and protect from freezing.

SAFETY FIRST! Always take appropriate steps to ensure the safety of your workshop environment.